



NANO-CLEAN

SURFACE CLEANER, It is a general-purpose cleaner developed for cleaning and removing the joint remnants on tiles rapidly and effectively in all kinds of ceramic applications.

USAGE AREAS

- Before painting, it is used for the preparation of metals and removal of the oil, dirt, and rust on metal surfaces.
- It removes the dirt in bathrooms, kitchens, and rooms without damaging the stainless steel and plastic surfaces.
- It should only be applied on stone, porcelain, ceramic, baked clay tiles as a joint cleaner.

APPLICATION INFORMATION

- The product is applied directly to the surface to be cleaned. (Joints, stucco coatings, metal surfaces, parts being processed, etc.)
- It is expected to penetrate for a maximum of 2-3 minutes. The oil, dirt, rust, stain etc. are removed by wiping with a sponge or cloth.
- If dirt is difficult, the application should be repeated and scrubbed with a brush or similar material.
- The surface should be thoroughly rinsed with plenty of water. In the case of metal cleaning, the protective agent should be applied immediately after cleaning.

CAUTIONS

The equipment to which it is applied must be made of acid-resistant material. It is recommended to test the product in a small area. **TAKE PROTECTIVE MEASURES AND WEAR GLASSES AND GLOVES DURING APPLICATION. THE PRODUCT IS IRRITATING TO THE EYES AND SKIN.** In case of contact with eyes, rinse immediately and seek medical advice.

CONSUMPTION: Variable according to the application

PACKAGING & STORAGE

- **Packaging** : 1 L, 5 L PE Drum
- **Storage temperature (°C)** : 5 - 35 °C
- **Shelf life** : 24 months from date of production if stored in original, unopened, undamaged packages.
- **Storage condition** : Store tightly closed in a dry and cool place.

! IMPORTANT

The equipment to which it is applied must be made of acid-resistant material. It is recommended to test the product in a small area. Take protective measures and wear glasses and gloves during application. The product is irritating to the eyes and skin. In case of contact with eyes, rinse immediately and seek medical advice.

APPLICATION CONDITIONS and RISKS







Things to consider during and after the application	Do not use together with other surface cleaning agents at the same time.
Other ISONEM products recommended	X
Application temperature	It should be applied between 5 - 35 °C.



General Features



Quick Clean

	 CONCRETE	 MARBLE, GRANITE	 RAW WOOD	 TILE, CERAMICS	 MEMBRANE, SHINGLE	 STEEL, METAL
Application	Spraying	X	X	Spraying	X	Spraying
Surface Humidity	X	X	X	X	X	X
Application Tools	Spray / Brush / Cloth	X	X	Spray / Brush / Cloth	X	Spray / Brush / Cloth
Primer Usage	X	X	X	X	X	X
Primer Consumption	X	X	X	X	X	X
Product Usage	X	X	X	X	X	X
Product Consumption	2 - 3 Minutes	X	X	2 - 3 Minutes	X	2 - 3 Minutes
Primer Consumption	X	X	X	X	X	X
Product Usage	X	X	X	X	X	X
Product Consumption	X	X	X	X	X	X

Note : Drying times are approximate data, it may vary depending on ambient conditions.

